


# U BOLT

**APPLICATION:**

U-Bolts are used to secure piping to structural members. When the piping is below the structural member, the U-Bolt provides vertical support and restricts lateral movement while allowing for axial movement. When the piping system is above the structural member, the U-Bolt restricts lateral movement and upward movement while allowing axial movement of the piping.



**CONSTRUCTION:**

U-Bolt is provided with four standard hex nuts and has a longer straight threaded length.

**MATERIAL:**

Mild Steel. Also other materials can be provided on request



**MAXIMUM TEMPERATURE:** 399°C (750°F)

**FINISH AVAILABLE:**

Electro-Galvanized, Hot Dip Galvanized, Plain

Product Code	Nominal Pipe Size		Pipe OD (mm)	Material Dimension(mm)			Bolt Size	MAX LOAD (KG)
	In.	mm		Rod Dia. W	Height L	T		
NAC-SUP128	½"	DN15	21.3	21	65	50	M10	750
NAC-SUP129	¾"	DN20	26.7	27	77	50	M10	750
NAC-SUP130	1"	DN25	33.4	34	85	50	M10	750
NAC-SUP131	1 ¼"	DN32	42.1	43	93	50	M10	750
NAC-SUP132	1 ½"	DN40	48.2	48	100	50	M10	750
NAC-SUP133	2"	DN50	60.3	60	110	50	M10	1250
NAC-SUP134	2 ½"	DN65	73	76	127	50	M12	1250
NAC-SUP135	3"	DN80	88.9	89	140	50	M12	1750
NAC-SUP136	4"	DN100	114.3	115	165	50	M12	1850
NAC-SUP137	6"	DN150	168.3	168	220	50	M12	2250
NAC-SUP138	8"	DN200	219.1	219	295	75	M16	2250
NAC-SUP139	10"	DN250	273	273	370	100	M20	3600
NAC-SUP140	12"	DN300	323.8	324	324	100	M20	3600
NAC-SUP141	16"	DN400	406.4	406	505	100	M20	4500
NAC-SUP142	20"	DN500	508	508	605	100	M24	4500
NAC-SUP143	24"	DN600	609.6	610	710	100	M24	5800