

HALF SADDLE

APPLICATION:

Recommended for support of standard conduit, cable and steel pipe on walls or sides of beams. Not recommended for use horizontally on ceilings, bottoms of beams and similar installations since the factor of safety is greatly reduced when so used.

CONSTRUCTION:

HALF SADDLE consists of single piece of mild steel shaped to proper configuration as shown in above diagram.



MATERIAL:

Mild Steel. Also other materials can also be provided on request.

FINISH AVAILABLE:

Electro-Galvanized, Hot dip Galvanized & Pregalvanized, Plain .

PRODUCT CODE	NOMINAL (INCH)	PIPE SIZE (MM)	DIA (MM)	SCREW
NAC-HS 15	1/2"	DN 15	21.3	M 6
NAC-HS 20	3/4"	DN 20	26.7	M 6
NAC-HS 25	1"	DN 25	33.4	M 6
NAC-HS 32	1 1/4"	DN 32	42.1	M 6
NAC-HS 40	1 1/2"	DN 40	48.2	M 6
NAC-HS 50	2"	DN 50	60.3	M 6
NAC-HS 65	2 1/2"	DN 65	73	M 6
NAC-HS 80	3"	DN 80	55.9	M 6
NAC-HS 100	4"	DN 100	114.3	M 6
NAC-HS 150	6"	DN 150	168.3	M 6