

LIGHT SADDLE

APPLICATION:

LIGHT SADDLE is recommended for supporting a piping system with vertically or horizontally to walls or ceilings.

CONSTRUCTION:

A LIGHT SADDLE consists of single piece of mild steel shaped to the proper configuration as shown in the diagram.



MATERIAL:

Mild Steel. Also other materials can also be provided on request.

FINISH AVAILABLE:

Electro-Galvanized, Hot dip Galvanized & Pregalvanized, Plain .

PRODUCT CODE	NOMINAL (INCH)	PIPE SIZE (MM)	DIA (MM)	SCREW
NAC-LS 15	1/2"	DN 15	21.3	M 6
NAC-LS 20	3/4"	DN 20	26.7	M 6
NAC-LS 25	1"	DN 25	33.4	M 6
NAC-LS 32	1 1/4"	DN 32	42.1	M 6
NAC-LS 40	1 1/2"	DN 40	48.2	M 6
NAC-LS 50	2"	DN 50	60.3	M 6
NAC-LS 65	2 1/2"	DN 65	73	M 6
NAC-LS 80	3"	DN 80	55.9	M 6
NAC-LS 100	4"	DN 100	114.3	M 6
NAC-LS 150	6"	DN 150	168.3	M 6