

PIPE HANGER WITHOUT LINING

APPLICATION:

PIPE HANGER is recommended for non-insulated stationary pipe lines in either a horizontal or vertical position. It can be used for supporting pipes along with roof as well as wall.

CONSTRUCTION:

PIPE HANGER consists of piece of mild steel shaped to wrap around the pipe. The selection of the proper 3-Bolt PIPE CLAMP depends upon the temperature of the piping system and load to be carried. Permits installation before and after pipe is in place.



MATERIAL:

Mild Steel. Also other materials can also be provided on request.

FINISH AVAILABLE:

Electro-Galvanized, Hot dip Galvanized & Pregalvanized, Plain .

Product Code	Pipe Size	Range	Thickness x Width	Side Screw	Top Nut	Hanger Bolt	Plastic Plug
NAC-LDNC 22	1/2"	20-24	2.0 x 20	M6 x 16	M 8	M8 x 80	S10 x 50
NAC-LDNC 27	3/4"	25-28	2.0 x 20	M6 x 16	M 8	M8 x 80	S10 x 50
NAC-LDNC 34	1"	23-35	2.0 x 20	M6 x 16	M 8	M8 x 80	S10 x 50
NAC-LDNC 42	1 1/4"	39-46	2.0 x 20	M6 x 16	M 8	M8 x 80	S10 x 50
NAC-LDNC 48	1 1/2"	48-53	2.0 x 20	M6 x 16	M 8	M8 x 80	S10 x 50
NAC-LDNC 60	2"	59-66	2.0 x 20	M6 x 16	M 8	M8 x 80	S10 x 50
NAC-LDNC 73	2 1/2"	74-80	2.0 x 25	M6 x 16	M 10	M10 x 100	S14 x 75
NAC-LDNC 89	3"	87-94	2.0 x 25	M6 x 16	M 10	M10 x 100	S14 x 75
NAC-LDNC 114	4"	107-115	2.0 x 25	M6 x 16	M 10	M10 x 100	S14 x 75
NAC-LDNC 168	6"	162-170	2.5 x 25	M6 x 16	M 10	M10 x 100	S14 x 75