


RISER CLAMP WITH LINING

APPLICATION:

RISER CLAMPS WITH LINING are recommended for the support and/or restraint of vertical steel pipes. A RISER CLAMP with lining is designed to attach to the pipe and to rest on a structural member or floor; It is not designed to have hanger rods attached to it to support the pipe.



CONSTRUCTION:

RISER CLAMPS WITH LINING consists of two mild steel flat bars bent to shape and held together by two bolts. Designed to act as a rigid support or guide for vertical pipes. The clamp should be bolted to the pipe just below support lugs or other attachments that can carry a shear load. Reduces noise upto 18dB.



MATERIAL:

Mild Steel. Also other materials can also be provided on request.

FINISH AVAILABLE:

Electro-Galvanized, Hot dip Galvanized & Pregalvanized, Plain .

| Product Code | Nominal Pipe Size | | Pipe OD (mm) | Length between Hole centre (mm) | Bolt Size | MAX LOAD (KG) |
|--------------|-------------------|-------|--------------|---------------------------------|-----------|---------------|
| | In. | mm | | | | |
| NAC-RCL15 | ½" | DN15 | 21.3 | 57 | M10 | 750 |
| NAC-RCL20 | ¾" | DN20 | 26.7 | 68 | M10 | 750 |
| NAC-RCL25 | 1" | DN25 | 33.4 | 76 | M10 | 750 |
| NAC-RCL32 | 1 ¼" | DN32 | 42.1 | 90 | M10 | 750 |
| NAC-RCL40 | 1 ½" | DN40 | 48.2 | 110 | M10 | 750 |
| NAC-RCL50 | 2" | DN50 | 60.3 | 130 | M10 | 1250 |
| NAC-RCL65 | 2 ½" | DN65 | 73 | 142 | M12 | 1250 |
| NAC-RCL80 | 3" | DN80 | 88.9 | 161 | M12 | 1750 |
| NAC-RCL100 | 4" | DN100 | 114.3 | 190 | M12 | 1850 |
| NAC-RCL150 | 6" | DN150 | 168.3 | 258 | M16 | 2250 |
| NAC-RCL200 | 8" | DN200 | 219.1 | 333 | M16 | 2250 |
| NAC-RCL250 | 10" | DN250 | 273 | 409 | M16 | 3600 |
| NAC-RCL300 | 12" | DN300 | 323.8 | 467 | M20 | 3600 |
| NAC-RCL400 | 16" | DN400 | 406.4 | 583 | M20 | 4500 |
| NAC-RCL500 | 20" | DN500 | 508 | 708 | M20 | 4500 |
| NAC-RCL600 | 24" | DN600 | 609.6 | 833 | M20 | 5800 |